



# TO-92 Plastic-Encapsulate Transistors

## BF423 TRANSISTOR ( NPN )

### FEATURES

Power dissipation

$$P_{CM}: 0.83 \text{ W (Tamb=25}^\circ\text{C)}$$

Collector current


$$I_{CM}: 0.1 \text{ A}$$

Collector-base voltage

$$V_{(BR)CBO}: 250 \text{ V}$$

Operating and storage junction temperature range

$$T_J, T_{stg}: -55^\circ\text{C to } +150^\circ\text{C}$$



### ELECTRICAL CHARACTERISTICS (Tamb=25°C unless otherwise specified)

Parameter	Symbol	Test conditions	MIN	TYP	MAX	UNIT
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C=100\mu\text{A}, I_E=0$	250			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C=1\text{mA}, I_B=0$	250			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E=100\mu\text{A}, I_C=0$	5			V
Collector cut-off current	$I_{CBO}$	$V_{CB}=200\text{ V}, I_E=0$			0.01	$\mu\text{A}$
Emitter cut-off current	$I_{EBO}$	$V_{EB}=5\text{ V}, I_C=0$			0.05	$\mu\text{A}$
	$H_{FE(1)}$	$V_{CE}=20\text{V}, I_C=25\text{mA}$	50			
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C=30\text{mA}, I_B=5\text{mA}$			0.6	V
Transition frequency	$f_T$	$V_{CE}=10\text{V}, I_C=10\text{mA}$ $f=100\text{MHz}$	60			MHz

### CLASSIFICATION OF HFE

Rank	1	2
Range	50-100	100-200