



TO-92 Plastic-Encapsulate Transistors

MPS751 TRANSISTOR (NPN)

FEATURES

Power dissipation

$$P_{CM}: 0.625 \text{ W (Tamb=25}^\circ\text{C)}$$

Collector current


$$I_{CM}: 2.0 \text{ A}$$

Collector-base voltage

$$V_{(BR)CBO}: 80 \text{ V}$$

Operating and storage junction temperature range

$$T_J, T_{stg}: -55^\circ\text{C to } +150^\circ\text{C}$$



ELECTRICAL CHARACTERISTICS (Tamb=25°C unless otherwise specified)

Parameter	Symbol	Test conditions	MIN	TYP	MAX	UNIT
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C=100\mu\text{A}, I_E=0$	-80			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C=10\text{mA}, I_B=0$	-60			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E=10\mu\text{A}, I_C=0$	-5			V
Collector cut-off current	I_{CEO}	$V_{CB}=30\text{V}, I_B=0$			100	μA
Emitter cut-off current	I_{EBO}	$V_{EB}=3\text{V}, I_C=0$			100	μA
DC current gain(note)	$H_{FE(1)}$	$V_{CE}=2\text{V}, I_C=50\text{mA}$	75			
DC current gain(note)	$H_{FE(2)}$	$V_{CE}=2\text{V}, I_C=500\text{mA}$	75			
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C=2\text{A}, I_B=200\text{mA}$			-0.5	V
Base-emitter saturation voltage	$V_{BE(sat)}$	$I_C=1\text{A}, I_B=100\text{mA}$			-0.3	V
Base-emitter voltage	V_{BE}	$V_{CE}=5\text{V}, I_C=2\text{mA}$			-1.0	V
Transition frequency	f_T	$V_{CE}=5\text{V}, I_C=50\text{mA}$ $f=1000\text{MHz}$	75			MHz

CLASSIFICATION OF HFE

Rank	1	C	D
Range	75-100	120-150	150-200